

**METHOD AND SYSTEM FOR INTERLEAVING OCR AND ABL FOR  
AUTOMATED MAIL SORTING**

**Field of the Invention**

5 The present invention relates to automated mail sorting and, more particularly, to methods and systems for increasing reading rates and lowering error rates by correlation between optical character recognition and address block location techniques.

**Background of the Invention**

10 In automated mail sorting systems, the ZIP code of the destination address on post mail, e.g., a letter or a parcel, has to be found. This is usually done by evaluating a digital image of the relevant surface of the piece of mail. This evaluation comprises firstly a procedure called Address Block Location (ABL) which locates a portion of the surface which looks like an address block, or has at least some similarity to it. Then, this portion is selected and passed to an Optical Character Recognition (OCR) system for further  
15 processing aimed to extract a ZIP code associated with the destination address of the post mail so that a sorting machine can sort the mail according to the ZIP code.

20 In prior art sorting machines, electronic programs running on a computer associated with the sorting machine are implemented to perform the ABL and said OCR procedures after a digital picture has been taken of the letter's or parcel's relevant surface area.

25 Such a system is disclosed in WO 98 17 405, the disclosure of which is incorporated by reference herein. The above-mentioned procedures are performed sequentially, first ABL, and then OCR. With a great portion of letters or parcels, such systems work quite well even though there remains an error rate which is always worth being lowered. Errors are very often due to confusing the destination address with the return address, both written on the surface.

Problems arise when the size of the envelope or one of the parcels is larger than about DIN B5, as may be the case, very often, particularly with parcels where further remarks, emblems, stamps or the like are printed on the surface. This can be misleading for such ABL systems because any of such emblems or remarks can be interpreted as a potential address block which is then passed to the OCR system and will be evaluated in vain as a destination address block.

### Summary of the Invention

Therefore, an object of the present invention is to provide a method and system for increasing reading rates and lowering error rates.

It is another object of the present invention to provide such method and system with increased processing speed.

According to the present invention, an improved method and system for automated sorting machines is provided in which a feedback between OCR and ABL takes place. According to a first aspect of the present invention, a loose coupling between ABL and OCR is proposed in which the ABL system is asked for a further address block potentially present on the letter's or parcel's surface when the first one being passed from ABL to OCR yielded a result that no destination ZIP code could be extracted from it. Thus, a first result of a first OCR procedure is fed back to the ABL system as a trigger signal in order to restart the ABL for providing the OCR system with a second proposal for a destination address block.

The 'restart ABL' decision is based advantageously on at least one of the following types of information described below.

The decision may be based on the confidence of the actual OCR result, i.e., how good was the first 'address block object' readable result. Thus, misleading address blocks, e.g., emblems having the outer shape of an address block (e.g., a rectangle filled with small symbols or characters), can be excluded as a sorting criterion as blocks which actually do not comprise any ZIP code or the name of a town.

Further, as the address block contents are known after being processed by the OCR procedure, any character information recognized by the OCR can be evaluated with some additional criteria based on general knowledge. For example, if the address block contents comprise a character string like 'Fax' or 'Phone,' it can be derived, with a high probability, that the actual address block represents the return address instead of the destination address. It is obvious that a lot of further examples for knowledge-based criteria can be found and used.

Further, ABL confidence is evaluated primarily with respect to the position, size, outer shape and inner structure found with the address block.

Further, the sort plan actually loaded on the concerned sorting machine can be visited for gathering more information. It holds information on incoming and outgoing mail, and on the town and its ZIP code in which the sorting machine is placed. Thus, assuming the local town in which the machine is installed is a small town and the ZIP code evaluated by the first run of the OCR is that of said small town, the probability is high that the found address block is the return address and must thus be rejected as a destination address. The larger the town, e.g., a city, the less reliable will be such a conclusion as, for example, in London, UK, many letters are destined to another location in London.

Similarly, postmark information can be evaluated as the stamp visible on a postmark designates the name and/or the ZIP code of the town in which the letter was stamped, which is in most cases the return address town.

Such evaluations can be performed and qualified in various ways independent of the concepts of the present invention. In order to concentrate on the real core of these concepts, only a simple and exemplary way is given below on how to qualify these evaluations for a conclusive decision whether or not to accept an address block as a destination address. To do that, some qualifying results (intermediate or final results) are constructed in the form of so-called 'confidence values,' further referred to as CF-value (i),  $i = 1, 2, \dots, 4$ , which are, e.g., normalized between zero (0) and one (1). Zero (0)

means that no indication can be derived from the evaluated information for having found a destination address block, and one (1) means a strong indication for having found a destination address. These CF-values (i) represent intermediate results related each to some special information evaluated. In order to get a usable total qualification of an address block, all intermediate results are considered, compared to each other and are evaluated including many particular context conditions which in turn are dependent from case to case. Thus, for example, by multiplication of all CF(i)-values, a CF-total value can be yielded. A CF-total of 1.0 would then mean that the destination address block is found with a probability of nearly 100%.

With reference back to the restart of the ABL system, the step of restarting the ABL system can be, of course, repeated as long as the available processing time allows it until a destination ZIP code can be extracted having a high probability of correctness.

The methodology of the present invention has the advantage, as compared to the above-described prior art technique, that the error rate is decreased due to the feedback of information from the OCR result to the ABL system. Consequently, the costs for manually sorting are reduced.

In a preferred embodiment of the invention, an ABL system continues to search further address blocks while the OCR system processes one or a plurality of address blocks being passed to it from the ABL system in a preceding procedure related to the same letter. After being processed by the OCR procedure, a summarizing ranking is calculated for each potential address block found. The best rank is given for the most probable destination address block. In this 'tight' coupling of ABL and OCR processes, basically the same criteria as mentioned above can be used. However, as a further advantage, the ABL and the OCR processes can be performed concurrently, except the first ABL process which is the required input for the first run of any OCR procedure. A feedback from ABL to OCR or to an OCR-and-ABL-embedding 'calling' program part can advantageously be provided in order to signal to the OCR and to said caller program part that no more reliable address blocks can be found. This represents a bi-directional

feedback between both OCR and ABL which can, of course, be interleaved as well. The feedback actions can be passed directly from ABL to OCR or, via the embedding caller program part from which ABL and OCR processes are controlled and invoked, respectively.

5           Thus, overall processing time is decreased in relation to the work which is done. Further, as all potential address blocks are analyzed, the error rate can be further reduced.

These and other objects, features and advantages of the present invention will become apparent from the following detailed description of illustrative embodiments thereof, which is to be read in connection with the accompanying drawings.

#### 10       **Brief Description of the Drawings**

FIG. 1 is a schematic representation of a block diagram showing the steps and the control flow of a method according to a first aspect (loose coupling) of the invention;

FIG. 2 is a schematic representation of a block diagram showing the steps and the control flow of a method according to a second aspect (tight coupling) of the invention;

15           FIG. 3 is a sketch of an envelope front side which may be subjected to the methods according to the first and second aspect of the invention; and

FIG. 4 is a block diagram illustrating a generalized hardware architecture of a computer system suitable for implementing methodologies according to the present invention.

20

#### **Detailed Description of Preferred Embodiments**

With general reference to the figures and with special reference now to FIG. 1, the steps of a method according to the invention are described next below.

25           It is assumed that a large size letter is subjected to the automated sorting machine having a computer associated therewith for implementing one or more programs for performing the methodology of the invention. For instance, the letter may be destined to an address having the ZIP code of Munich, Germany and having a return address with the

ZIP code of Stuttgart, Germany. Both respective address blocks may be present on the letter, but, exemplarily, both blocks may be nearly equal in size and, complicating the case, the destination address block may be placed at an unusual location at the left lower corner of the envelope. Further, the return address block may comprise the words:  
5 'please notify' and 'FAX 0711-89898989, z.H., Hr. Maier'. It may also be further assumed that the postmark information discloses a ZIP code relating to Stuttgart as well, and that a remark:

ATTENTION !

HANDLE

WITH

CARE

is visible at a location at which usually the destination address is found.

In a first step, the letter is subjected to the initial ABL procedure (step 110). As the remark:

ATTENTION !

HANDLE

WITH

CARE

has nearly the outer shape of a rectangle and is found on the usual location of the destination address block, the ABL processing will offer that remark first to the OCR procedure, steps 110 and 120 (Yes branch). The pattern is thus processed by OCR. As 100% of the characters comprising the pattern were recognized, the pure OCR quality is qualified as very well. As, however, the remark does not comprise any ZIP code, no good confidence rating, in the form of the above-mentioned confidence value CF-Value



Stuttgart and it is decided that the current address block can still be the destination address block with a forgotten ZIP-code. In conclusion, a balanced value of, e.g., 0.5 is assigned as a CF(3) value.

Then, in a step 160, the postmark information is checked by ABL and OCR. It is assumed to reveal Stuttgart and a respective ZIP code as the town where the letter was stamped. Thus, the information gathered in conjunction with step 150 is further affirmed, and the same value of 0.5 is assigned as CF(4) value.

Then, advantageously, a cross-check of a table comprising towns and their respective ZIP code can be performed in order to see, if 'CARE' is the name of a town in Germany or within a region in Europe, or worldwide, respectively. It is assumed that the result is negative, a town 'CARE' is unknown. Also, optionally, a cross-check of expressions often found in warnings or further remarks written on letters or parcels is performed which would, of course, comprise the text pattern 'handle with care'.

Then, a comprehensive intermediate conclusion is undertaken, primarily respecting the fact whether a ZIP code could be extracted from the processed address block. It should be understood that, generally, there might be respected the results found in steps 140, 150, 160, as well, for example in cases in which the OCR result is quite ambiguous, when, e.g., the ZIP code of the town has such a large distance to the name of the town that only the town name is recognized as a part of the current address block. This can then in turn be taken as a trigger for restarting the ABL system for locating the missing ZIP-code directly and feeding it separately to the OCR system as an annex to the address block currently being processed.

Thus, back to the case depicted in FIG. 3 and explained in the context of FIG. 1, it is decided in a decision step 170 that a further address block is asked for from the ABL system without performing a particular complex CF-total calculation as depicted in step 180 which however will be done and described with the next address block. Thus, a direct feedback step happens from OCR to ABL, and ABL is restarted via the NO branch of step 170.







address block directly from being proposed as a destination address block. Thus, the currently found address block is proposed as the destination address block of the letter and the ZIP code of Munich is output to the sorting machine for sorting the letter into the respective folder designated for Munich (step 200). Then, the sorting procedure is completed (step 210).

With additional reference now to FIG. 2, a second aspect of the present invention disclosing a tight coupling between ABL and OCR processes is described next below.

Here, the ABL system first processes the remark 'ATTENTION! HANDLE WITH CARE' (steps 310, 320). This potential address block is passed to the OCR system for further processing, i.e., for performing the steps described in conjunction with steps 130, 150 and 160 of FIG. 1, as depicted in step 330 of FIG. 2. The way to process the address block is basically the same as that one described above, i.e., CF(i) values are calculated and assigned to the address block found. As depicted in step 340, however, in contrast to the above-described procedure, the CF(i) values are collected and saved in a dedicated storage area for a ranking made up between further address blocks still to be found during concurrent processing of the ABL system, i.e., the second YES branch leading to the next looking run of the ABL system (step 310).

Thus, the ABL system continues to search further address blocks - here, the next block is that one with the return address - while the OCR system may still process the first one. Optionally, a buffer memory is provided for storing data the ABL system has retrieved and which the OCR system is not yet able to process.

As will be appreciated by a person skilled in the art, the processes of the ABL and the OCR systems are concurrent in time which represents the tight coupling between them and which yields a great advantage compared to the prior art, i.e., efficiently using the computational resources present in the automatic sorting machine's computer system.

Finally, no more address blocks are found in decision step 320. All address blocks present on the letter's surface have now been located by the ABL system. This can be a decisive difference to the embodiment just described above which terminates ABL

activity when - deviating from the example given in FIG. 3 - an address block is found which is qualified by the embedding calling program as good enough for being accepted as a destination address block. In such a case, a further address block might be found later in time which is considered to have a higher probability to be the destination address block than the block having the relatively good probability found before.

After all address blocks are processed by the OCR procedure, the embedding program calculates a summarizing ranking covering each potential address block found (step 360). The ranks are compared and the best rank is used as an indication for the most probable destination address block, the ZIP code of which is output for sorting the letter properly (step 370). Then, the sorting procedure is completed (step 380).

Referring now to FIG. 4, a block diagram is shown illustrating a generalized hardware architecture of a computer system suitable for implementing the methodologies of the present invention. That is, the illustrative architecture depicts the computational resources present in the automatic sorting machine's computer system wherein the methodologies described herein including the ABL and OCR procedures may be executed. Of course, such methodologies may be implemented on more than one such computer system.

As shown, the computer system 400 may be implemented in accordance with a processor 402, a memory 404 and I/O devices 406. It is to be appreciated that the term "processor" as used herein is intended to include any processing device, such as, for example, one that includes a CPU (central processing unit) and/or other processing circuitry. The term "memory" as used herein is intended to include memory associated with a processor or CPU, such as, for example, RAM, ROM, a fixed memory device (e.g., hard drive), a removable memory device (e.g., diskette), flash memory, etc. In addition, the term "input/output devices" or "I/O devices" as used herein is intended to include, for example, one or more input devices, e.g., keyboard, for entering data to the processing unit, and/or one or more output devices, e.g., CRT display and/or printer, for presenting results associated with the processing unit. The I/O devices may also include

002080-09633604

a scanning device for capturing the digital image of the mail surface to be processed. It is also to be understood that the term "processor" may refer to more than one processing device and that various elements associated with a processing device may be shared by other processing devices. Accordingly, software components including instructions or code for performing the methodologies, as described herein, may be stored in one or more of the associated memory devices (e.g., ROM, fixed or removable memory) and, when ready to be utilized, loaded in part or in whole (e.g., into RAM) and executed by a CPU.

In the foregoing specification, the invention has been described with reference to two specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are accordingly to be regarded as illustrative rather than in a restrictive sense.

In particular, the control flow depicted in the drawings should be regarded as illustrative only. Many variations are possible to achieve the same abstract goals, i.e., providing a feedback from OCR to ABL and/or to run ABL and OCR processes concurrently in time.

Further, many exclusive conditions can be retrieved which exclude an address block from being further processed and treated as a potential destination address block. Into such knowledge-based conditions, all general knowledge can be imported which has accumulated in the post offices all over the world. And, finally, it will be appreciated that those conditions will vary from country to country or from continent to continent.